

**FLEXIBLE CORD
 PVC TRURIP
 (TWIN FLEX)**



APPLICATION For connection to non-metallic appliances where no earthis required and the current drawn is low, e.g. table lamps, radios and pendants etc.	STANDARD	0.50mm ² NZS 6402:1973 0.75mm ² AS/NZS
	VOLTAGE	0.50mm ² 300/300V 0.75mm ² 250/250V
	CONDUCTOR	Annealed Copper
	INSULATION	PVC, V-90 White with Red stripe
	MAX. OPERATING TEMP.	75°C

Item Number	Conductor		Overall Diameter		Approx Mass Per Kg/km
	Nominal Area mm ²	Number & Diameter of Wires (No./mm)	Min	Max	
			Major x minor mm	Major x minor mm	
DC911	0.5	16/0.2	5.3 X 2.5	5.7 X 2.7	25
DC921	0.75	24/0.2	5.7 X 2.7	6.0 X 2.9	35
DC942 T/F	1.5	30/0.25	6.5 X 3.0	6.8 X 3.3	45

Do not put in direct contact with polystyrene, polyurethane or similar thermal insulation materials.

CONDUCTOR	Min Insulation Thickness	Current Rating	Voltage Drop
Nominal Area mm ²	mm	A	Mv/Am
0.5	0.8	3	94.9
0.75	0.8	7.5	63.3
1.5	0.8	15	30.8

DOMINION WIRE & CABLES LTD.

QUALITY CABLE MANUFACTURES, DISTRIBUTORS AND EXPORTERS

LOT 3, KINGS ROAD, YALALEVU, BA. P.O. BOX 1562, BA, FIJI.

PHONE: (679)6675244 FAX: (679)6670023,

E-Mail: sales@dominioncables.com

web: www.dominioncables.com

Dominion Cables is a leader in the Cable Industry. The services of sales and technical staff are always available to assist with any enquiry. The Dominion Cables policy is one of continual improvement. Details as published may be subject to change.

This brochure is distributed with the understanding that the authors and editors are not responsible for the results of any action taken on the basis of information in this work, or any errors or omissions. Further, Dominion Cables is not engaged in rendering professional services. Dominion Cables expressly disclaims all and any liability to any person in respect of anything and of the consequences of anything done or omitted to be done by any such person in reliance whether whole or partial of the whole or any part of the contents of this publication. All rights reserved.