



APPLICATION

Easi-peel sheath for general wiring, unenclosed, in conduit, buried direct or in underground ducts for domestic, commercial and industrial installations where not subject to mechanical damage.

STANDARD VOLTAGE

AS/NZS 5000.2
450/750V

CONDUCTOR INSULATION

Copper 1 - 16mm²
PVC, V-90
Red & Black or Red & White

SHEATH

PVC, 3V-90
White

MAX. OPERATING TEMP.

90 °C

Product Code	Insulation Colour	Conductor		Overall Diameter	Approx. Mass kg/km	Minimum Installed Bending Radius mm
		mm ²	(No./mm)	Nominal mm		
DC209 R/B	Red+Black	1	1/1.13	4.3 x 6.7	60	40
DC209 R/W	Red+White	1	1/1.13	4.3 x 6.7	60	40
DC229 R/B	Red+Black	1.5	7/0.50	4.7 x 7.4	80	50
DC229 R/W	Red+White	1.5	7/0.50	4.7 x 7.4	80	50
DC249 R/B	Red+Black	2.5	7/0.67	5.5 x 9.0	100	55
DC249 R/W	Red+White	2.5	7/0.67	5.5 x 9.0	100	55
DC259 R/B	Red+Black	4	7/0.85	6.5 x 10.6	140	65
DC259 R/W	Red+White	4	7/0.85	6.5 x 10.6	140	65
DC269 R/B	Red+Black	6	7/1.04	7.0 x 11.7	200	75
DC269 R/W	Red+White	6	7/1.04	7.0 x 11.7	200	75
DC279 R/B	Red+Black	10	7/1.35	8.5 x 14.4	400	90
DC279 R/W	Red+White	10	7/1.35	8.5 x 14.4	400	90
DC289 R/B	Red+Black	16	7/1.70	9.7 x 16.7	600	100