



**APPLICATION**

Easi-peel sheath for general wiring unenclosed, enclosed in conduit, buried direct or in underground ducts for domestic, commercial and industrial installations where not subject to mechanical damage.

**STANDARD VOLTAGE**

AS/NZS 5000.2  
450/750V

**CONDUCTOR INSULATION**

Copper 1 - 16mm<sup>2</sup>  
PVC, V-90  
Red, Black & Green/Yellow

**SHEATH**

PVC, 3V-90  
White

**MAX. OPERATING TEMP.**

90 °C

Product Code	Conductor		Overall Diameter	Approx. Mass kg/km	Minimum Installed Bending Radius mm
	mm <sup>2</sup>	(No./mm)	Nominal mm		
DC309	1	1/1.13	4.5 x 9.5	85	55
DC329	1.5	7/0.50	4.7 x 10.2	115	65
DC339	2.5	1/1.78	5.8 x 12.0	140	70
DC349	2.5	7/0.67	5.5 x 12.4	150	75
DC359	4	7/0.85	6.5 x 14.0	220	85
DC369	6	7/1.04	7.1 x 15.2	270	95
DC379	10	7/1.35	8.5 x 18.6	440	115
DC389	16	7/1.70	10.0 x 21.3	500	130