



APPLICATION Suitable for all fixed Wiring switchboard/control panel applications. Significant reduction in wiring installation time due to flexibility and ease of handling.	STANDARD VOLTAGE	AS/NZS 5000.1 600/1000V
	CONDUCTOR INSULATION	Copper 1 - 150mm ² PVC, V-90 See below for colour options
	MAX. OPERATING TEMP.	90°C

Product Code	Conductor		Overall Diameter Maximum (Approx.) mm	Standard Packing	
	mm ²	(No./mm)		100m	500m
DC93x	1	32/0.20	3.1	✓	
DC94x	1.5	48/0.20	3.4	✓	
DC95x	2.5	80/0.20	4.1	✓	
DC96x	4	50/0.32	5.0	✓	
DC96x	6	77/0.32	5.40	✓	
DC97x	10	125/0.32	6.60	✓	
DC98x	16	196/0.32	7.60	✓	
DC100x	25	311/0.32	9.30	✓	
DC101x	35	434/0.32	10.40	✓	
DC102x	50	622/0.32	12.40		✓
DC103x	70	871/0.32	14.30		✓
DC104x	95	1181/0.32	16.50		✓
DC105x	120	1493/0.32	18.30		✓
Dc106x	150	756/0.50	20.90		✓

x=1 for Black
 x=2 for Red
 x=3 for White

x=4 for Blue
 x=5 for Green/Yellow

NB: We may not stock all sizes in all colour variations
 Bigger Size available on request