



APPLICATION

Easi-peel sheath for general wiring, unenclosed, in conduit, buried direct or in underground ducts for domestic, commercial and industrial installations where not subject to mechanical damage.

Suitable for glanding.

STANDARD VOLTAGE

AS/NZS 5000.2
450/750V

CONDUCTOR INSULATION

Copper 1 – 25mm²
PVC, V-90
Black, Red or White

SHEATH

PVC, 3V-90
White (25mm² White or Black)

MAX. OPERATING TEMP.

90°C

Product Code	Conductor		Overall Diameter		Approx. Mass Kg/Km	Minimum Installed Bending Radius mm
	mm ²	(No./mm)	Minimum (mm)	Maximum (mm)		
DC109/y	1	1/1.13	3.9	4.2	20	20
DC129/y	1.5	7/0.50	4.3	4.6	25	20
DC149/y	2.5	7/0.67	5.0	5.3	35	25
DC159/y	4	7/0.85	5.9	6.2	55	30
DC169/y	6	7/1.04	6.4	6.8	70	35
DC179/y	10	7/1.35	7.6	8.1	120	40
DC189/y	16	7/1.70	8.9	9.4	180	45
DC199/y	25	19/1.35	11.0	11.5	285	60

y= 1 for Black
y= 2 for Red
y= 3 for White